

Features

- Compact Metal Case with Excellent Thermal Performance
- Full Power at Wide Output Current Range (Constant Power)
- Adjustable Output Current (AOC) with Programmability
- Isolated 1-5V/1-10V/10V PWM/3-Timer-Modes Dimmable
- Output Lumen Compensation
- Input Surge Protection: DM 6kV, CM 10kV
- All-Around Protection: OVP, SCP, OTP
- IP66 / IP67 and UL Dry / Damp / Wet Location
- SELV Output
- TYPE HL, for use in a Class I, Division 2 hazardous (Classified) location
- 5 Years Warranty



Description

The EUM-150SxxxDx series is a 150W, constant-current, programmable and IP66/IP67 rated LED driver that operates from 90-305Vac input with excellent power factor. It is created for many lighting applications including high bay, high mast and roadway, etc. The high efficiency of these drivers and compact metal case enables them to run cooler, significantly improving reliability and extending product life. To ensure trouble-free operation, protection is provided against input surge, output over voltage, short circuit, and over temperature.

Models

Adjustable Output Current Range	Full-Power Current Range (1)	Default Output Current	Input Voltage Range(2)	Output Voltage Range	Max. Output Power	Typical Efficiency (3)	Typical Power Factor		Model Number (5)
							120Vac	220Vac	
53-700mA	530-700mA	530mA	90~305 Vac/ 127~300 Vdc	107~284 Vdc	150W	93.5%	0.99	0.96	EUM-150S070Dx ⁽⁶⁾
70-1050mA	700-1050mA	700mA	90~305 Vac/ 127~300 Vdc	72~214 Vdc	150W	93.0%	0.99	0.96	EUM-150S105Dx
105-1500mA	1050-1500mA	1050mA	90~305 Vac/ 127~300 Vdc	50~143 Vdc	150W	93.5%	0.99	0.96	EUM-150S150Dx
140-2100mA	1400-2100mA	1400mA	90~305 Vac/ 127~300 Vdc	36~107 Vdc	150W	92.0%	0.99	0.96	EUM-150S210Dx ⁽⁴⁾
280-4200mA	2800-4200mA	3150mA	90~305 Vac/ 127~300 Vdc	18 ~ 54 Vdc	150W	91.5%	0.99	0.96	EUM-150S420Dx ⁽⁴⁾

Notes: (1) Output current range with constant power at 150W

(2) Certified input voltage range: UL, FCC 100-277Vac; otherwise 100-240Vac.

(3) Measured at 100% load and 220Vac input (see below "General Specifications" for details).


(4) SELV output.

(5) x = G are UL Recognized, ENEC and CCC, etc. models; x = T are UL Class P models; x = B are BIS models.


(6) Only available with x = G, and only with ENEC, CE, CB and CCC certificates.

I-V Operation Area


EUM-150S070Dx




EUM-150S105Dx




EUM-150S150Dx



EUM-150S210Dx



EUM-150S420Dx



Input Specifications

Parameter	Min.	Typ.	Max.	Notes
Input AC Voltage	90 Vac	-	305 Vac	
Input DC Voltage	127 Vdc	-	300 Vdc	
Input Frequency	47 Hz	-	63 Hz	
Leakage Current	-	-	0.75 MU	UL8750; 277Vac/ 60Hz
	-	-	0.70 mA	IEC60598-1; 240Vac/ 60Hz
Input AC Current	-	-	1.50 A	Measured at 100% load and 120 Vac input.
	-	-	0.80 A	Measured at 100% load and 220 Vac input.
Inrush Current(I ² t)	-	-	3.55 A ² s	At 220Vac input, 25°C cold start, duration=220 μs, 10%I _{pk} -10%I _{pk} . See Inrush Current Waveform for the details.
PF	0.9	-	-	At 100-277Vac, 50-60Hz, 65%-100% Load (97.5-150W)
THD	-	-	20%	
THD	-	-	10%	At 220-240Vac, 50-60Hz, 75%-100% Load (112.5-150W)

Output Specifications

Parameter	Min.	Typ.	Max.	Notes
Output Current Tolerance	-5%loset	-	5%loset	At 100% load condition
Output Current Setting(loset) Range				
EUM-150S070Dx	53 mA	-	700 mA	
EUM-150S105Dx	70 mA	-	1050 mA	
EUM-150S150Dx	105 mA	-	1500 mA	
EUM-150S210Dx	140 mA	-	2100 mA	
EUM-150S420Dx	280 mA	-	4200 mA	
Output Current Setting Range with Constant Power				
EUM-150S070Dx	530 mA	-	700 mA	
EUM-150S105Dx	700 mA	-	1050 mA	
EUM-150S150Dx	1050 mA	-	1500 mA	
EUM-150S210Dx	1400 mA	-	2100 mA	
EUM-150S420Dx	2800 mA	-	4200 mA	
Total Output Current Ripple (pk-pk)	-	5%lomax	10%lomax	At 100% load condition. 20 MHz BW
Output Current Ripple at < 200 Hz (pk-pk)	-	2%lomax	-	At 100% load condition. Only this component of ripple is associated with visible flicker.
Startup Overshoot Current	-	-	10%lomax	At 100% load condition
No Load Output Voltage				
EUM-150S070Dx	-	-	320 V	
EUM-150S105Dx	-	-	240 V	
EUM-150S150Dx	-	-	160 V	
EUM-150S210Dx	-	-	120 V	
EUM-150S420Dx	-	-	60 V	
Line Regulation	-	-	±0.5%	Measured at 100% load

Output Specifications (Continued)

Parameter	Min.	Typ.	Max.	Notes
Load Regulation	-	-	± 1.5%	
Turn-on Delay Time	-	-	0.5 s	Measured at 120-277Vac input, 65%-100% Load
Temperature Coefficient of Isolet	-	0.03%/°C	-	Case temperature = 0°C ~Tc max

General Specifications

Parameter	Min.	Typ.	Max.	Notes
Efficiency at 120 Vac input: EUM-150S070Dx Io= 530 mA Io= 700 mA EUM-150S105Dx Io= 700 mA Io=1050 mA EUM-150S150Dx Io=1050 mA Io=1500 mA EUM-150S210Dx Io=1400 mA Io=2100 mA EUM-150S420Dx Io=2800 mA Io=4200 mA	89.0% 90.0% 88.5% 89.0% 89.0% 89.5% 87.5% 88.0% 87.0% 86.5%	91.0% 92.0% 90.5% 91.0% 91.0% 91.5% 89.5% 90.0% 89.0% 88.5%	- - - - - - - - - -	Measured at 100% load and steady-state temperature in 25°C ambient; (Efficiency will be about 2.0% lower if measured immediately after startup.)
Efficiency at 220 Vac input: EUM-150S070Dx Io= 530 mA Io= 700 mA EUM-150S105Dx Io= 700 mA Io=1050 mA EUM-150S150Dx Io=1050 mA Io=1500 mA EUM-150S210Dx Io=1400 mA Io=2100 mA EUM-150S420Dx Io=2800 mA Io=4200 mA	91.0% 91.5% 90.5% 91.0% 91.0% 91.5% 89.5% 90.0% 89.5% 89.0%	93.0% 93.5% 92.5% 93.0% 93.0% 93.5% 91.5% 92.0% 91.5% 91.0%	- - - - - - - - - -	Measured at 100% load and steady-state temperature in 25°C ambient; (Efficiency will be about 2.0% lower if measured immediately after startup.)

General Specifications (Continued)

Parameter	Min.	Typ.	Max.	Notes
Efficiency at 277 Vac input: EUM-150S070Dx I _o = 530 mA I _o = 700 mA EUM-150S105Dx I _o = 700 mA I _o =1050 mA EUM-150S150Dx I _o =1050 mA I _o =1500 mA EUM-150S210Dx I _o =1400 mA I _o =2100 mA EUM-150S420Dx I _o =2800 mA I _o =4200 mA	91.5% 92.0% 91.0% 91.5% 91.5% 91.5% 90.0% 90.0% 89.5% 89.0%	93.5% 94.0% 93.0% 93.5% 93.5% 93.5% 92.0% 92.0% 91.5% 91.0%	- - - - - - - - - -	Measured at 100% load and steady-state temperature in 25°C ambient; (Efficiency will be about 2.0% lower if measured immediately after startup.)
MTBF	-	333,000 Hours	-	Measured at 220Vac input, 80%Load and 25°C ambient temperature (MIL-HDBK-217F)
Lifetime	-	106,000 Hours	-	Measured at 220Vac input, 80%Load and 70°C case temperature; See lifetime vs. T _c curve for the details
Operating Case Temperature for Safety T _{c_s}	-40°C	-	+90°C	
Operating Case Temperature for Warranty T _{c_w}	-40°C	-	+80°C	Case temperature for 5 years warranty Humidity: 10% RH to 95% RH;
Storage Temperature	-40°C	-	+85°C	Humidity: 5%RH to 95%RH
Dimensions Inches (L × W × H) Millimeters (L × W × H)	6.34 × 2.36 × 1.44 161 × 60 × 36.5			With mounting ear 7.01 × 2.36 × 1.44 178 × 60 × 36.5
Net Weight	-	735 g	-	

Dimming Specifications

Parameter		Min.	Typ.	Max.	Notes
Absolute Maximum Voltage on the Vdim (+) Pin		-20 V	-	20 V	
Source Current on Vdim (+)Pin		200 μA	300 μA	450 μA	Vdim(+) = 0 V
Dimming Output Range	EUM-150S070Dx EUM-150S105Dx EUM-150S150Dx EUM-150S210Dx EUM-150S420Dx	10%I _o set	-	I _o set	530 mA ≤ I _o set ≤ 700 mA 700 mA ≤ I _o set ≤ 1050 mA 1050 mA ≤ I _o set ≤ 1500 mA 1400 mA ≤ I _o set ≤ 2100 mA 2800 mA ≤ I _o set ≤ 4200 mA
	EUM-150S070Dx EUM-150S105Dx EUM-150S150Dx EUM-150S210Dx EUM-150S420Dx	53 mA 70 mA 105 mA 140 mA 280 mA	-	I _o set	53 mA ≤ I _o set ≤ 530mA 70 mA ≤ I _o set < 700 mA 105 mA ≤ I _o set < 1050 mA 140 mA ≤ I _o set < 1400 mA 280 mA ≤ I _o set < 2800 mA
Recommended Dimming Range for 1-5V		0.25 V	-	4.75 V	Dimming mode set to 1-5V in PC interface.
Recommended Dimming Range for 1-10V		1 V	-	9 V	Default 1-10V dimming mode with positive logic.

Dimming Specifications (Continued)

Parameter	Min.	Typ.	Max.	Notes
PWM_in High Level	-	10V	-	
PWM_in Low Level	-	0V	-	
PWM_in Frequency Range	200 Hz	-	2 KHz	
PWM_in Duty Cycle	0%	-	100%	

Safety & EMC Compliance


Safety Category	Standard
UL/CUL	UL8750,CAN/CSA-C22.2 No. 250.13
ENEC & CE	EN 61347-1, EN 61347-2-13
UKCA	BS EN 61347-1, BS EN 61347-2-13
CB	IEC 61347-1, IEC 61347-2-13
CCC	GB 19510.1, GB 19510.14
PSE	J 61347-1, J 61347-2-13
KS	KS C 7655
BIS	IS 15885(Part2/Sec13)
EAC	ГОСТ Р МЭК 61347-1, ГОСТ IEC 61347-2-13
NOM	NOM-058-SCFI
EMI Standards	Notes
EN 55015/GB 17743/KN 15 ⁽¹⁾	Conducted emission Test & Radiated emission Test
EN 61000-3-2/GB 17625.1	Harmonic current emissions
EN 61000-3-3	Voltage fluctuations & flicker
FCC Part 15 ⁽¹⁾	ANSI C63.4 Class B This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: [1] this device may not cause harmful interference, and [2] this device must accept any interference received, including interference that may cause undesired Operation.
EMS Standards	Notes
EN 61000-4-2	Electrostatic Discharge (ESD): 8 kV air discharge, 4 kV contact discharge
EN 61000-4-3	Radio-Frequency Electromagnetic Field Susceptibility Test-RS
EN 61000-4-4	Electrical Fast Transient / Burst-EFT

Safety & EMC Compliance (Continued)


EMS Standards	Notes
EN 61000-4-5	Surge Immunity Test: AC Power Line: Differential Mode 6 kV, Common Mode 10 kV
EN 61000-4-6	Conducted Radio Frequency Disturbances Test-CS
EN 61000-4-8	Power Frequency Magnetic Field Test
EN 61000-4-11	Voltage Dips
EN 61547	Electromagnetic Immunity Requirements Applies To Lighting Equipment

Note: (1) This LED driver meets the EMI specifications above, but EMI performance of a luminaire that contains it depends also on the other devices connected to the driver and on the fixture itself.


Derating







Lifetime vs. Case Temperature




Inrush Current Waveform




Efficiency vs. Load




EUM-150S150Dx($I_o=1050\text{mA}$)
Efficiency vs. Output Voltage




EUM-150S150Dx($I_o=1500\text{mA}$)
Efficiency vs. Output Voltage




EUM-150S210Dx($I_o=1400\text{mA}$)
Efficiency vs. Output Voltage




EUM-150S210Dx($I_o=2100\text{mA}$)
Efficiency vs. Output Voltage




EUM-150S420Dx($I_o=2800\text{mA}$)
Efficiency vs. Output Voltage




EUM-150S420Dx($I_o=4200\text{mA}$)
Efficiency vs. Output Voltage



Power Factor



Total Harmonic Distortion





Protection Functions

Parameter	Notes
Over Temperature Protection	Decreases output current, returning to normal after over temperature is removed.
Short Circuit Protection	Auto Recovery. No damage will occur when any output is short circuited. The output shall return to normal when the fault condition is removed.
Over Voltage Protection	Limits output voltage at no load and in case the normal voltage limit fails.

Dimming

● 1-5V Dimming

The recommended implementation of the dimming control is provided below.





Notes:



1. Do NOT connect Dim- to the output V- or V+, otherwise the driver will not work properly.
2. The dimmer can also be replaced by an active 1-5V voltage source signal or passive components like zener.
3. When 1-5V negative logic dimming mode and Dim+ is open, the driver will output maximum current.

● 1-10V Dimming

The recommended implementation of the dimming control is provided below.



Implementation 3: Positive logic





Implementation 4: Negative logic

Notes:


1. Do NOT connect Dim- to the output V- or V+, otherwise the driver will not work properly.
2. The dimmer can also be replaced by an active 1-10V voltage source signal or passive components like zener.
3. When 1-10V negative logic dimming mode and Dim+ is open, the driver will output minimum current.

● 10V PWM Dimming

The recommended implementation of the dimming control is provided below.



Implementation 5: Positive logic



Implementation 6: Negative logic

Notes:

1. Do NOT connect Dim- to the output V- or V+, otherwise the driver will not work properly.
2. When PWM negative logic dimming mode and Dim+ is open, the driver will output minimum current.

● Time Dimming

Time dimming control includes 3 kinds of modes, they are Self Adapting-Midnight, Self Adapting-Percentage and Traditional Timer.


- **Self Adapting-Midnight:** Automatically adjusts the dimming curve based on the on-time of past two days (if difference <15 minutes), assuming that the center point of the dimming curve is midnight local time.
- **Self Adapting-Percentage:** Automatically adjusts the on-time of each step by a constant percentage = (actual on-time for the past 2 days if difference <15 min) / (programmed on-time from the dimming curve).
- **Traditional Timer:** Follows the programmed timing curve after power on with no changes.

● Output Lumen Compensation


Output Lumen Compensation (OLC) may be used to maintain constant light output over the life of the LEDs by driving them at a reduced current when new, then gradually increasing the drive current over time to counteract LED lumen degradation.

Programming Connection Diagram


EUM-150SxxxDG



EUM-150SxxxDT



EUM-150SxxxDB




Note: The driver does not need to be powered on during the programming process.

- Please refer to [PRG-MUL2](#) (Programmer) datasheet for details.


Mechanical Outline

EUM-150S070/105/150DG



EUM-150S210/420DG

INPUT (UL SJOW 17AWG/3C & VDE H05RN-F 3*1.0mm² Ø8.3)




PROJ:

Unspecified tolerance: ± 1

EUM-150S105/150DT


INPUT(UL SJTW 3*18AWG Ø7.8)




PROJ:		
-------	---	---

Unspecified tolerance: ± 1


EUM-150S210/420DT



EUM-150S105/150DB



EUM-150S210/420DB



RoHS Compliance

Our products comply with reference to RoHS Directive (EU) 2015/863 amending 2011/65/EU, calling for the elimination of lead and other hazardous substances from electronic products.

Revision History

Change Date	Rev.	Description of Change		
		Item	From	To
2021-03-09	A	Datasheets Release	/	/
2021-07-08	B	Models	EUM-150S070Dx	Added
		I-V Operation Area	EUM-150S070Dx	Added
		Output Current Setting(Io _{set}) Range	EUM-150S070Dx	Added
		Output Current Setting Range with Constant Power	EUM-150S070Dx	Added
		No Load Output Voltage	EUM-150S070Dx	Added
		Efficiency at 120 Vac input:	EUM-150S070Dx	Added
		Efficiency at 220 Vac input:	EUM-150S070Dx	Added
		Efficiency at 277 Vac input:	EUM-150S070Dx	Added
		Dimming Output Range	EUM-150S070Dx	Added
		Efficiency vs. Load	EUM-150S070Dx	Added
		Mechanical Outline	EUM-150S070DG	Added
2021-07-22	C	Models	Notes(6)	Added
2021-12-13	D	UKCA logo	/	Added
		Safety & EMC Compliance	UKCA	Added
		Programming Connection Diagram	EUM-150SxxxDT	Updated
		Mechanical Outline	EUM-150S105/150DT	Updated
		Mechanical Outline	EUM-150S210/420DT	Updated