

1094

Post Top Luminaires


5 YEAR
WARRANTY





HEAT DISSIPATION PERFORMANCE


Advanced FEA technology designs for the structure thermal transfer to guarantee the LED PCB and chips can use for long life.



Non-contact structure for LED drivers and heat sinks. The electrical parts are in cool status.


Die-casting aluminum heat sinker is designed inside. The air convection structure enhances the lumen maintenance performance.

**THERMAL- ELECTRICAL
DIVIDED**





Light Distributions


3030 Version



5050 Version




Asymmetric
Optics






SUGGESTED INSTALLATION HEIGHT



CHARACTERS

Model No	ZGSM-1094A-40	ZGSM-1094A-60	ZGSM-1094B-80	ZGSM-1094B-100
Power	40W	60W	80W	100W
Protection Class	CLASS I/II			
IP/IK Rating	IP66, IK08			
Color Temperature	2200K-6500K	2200K-6500K	2200K-6500K	2200K-6500K
Efficiency(3030 Version)	110 LM/W	110 LM/W	125 LM/W	120 LM/W
Efficiency(5050 Version)	120 LM/W	120 LM/W	130 LM/W	130 LM/W
CRI	70/80	70/80	70/80	70/80
Input Voltage	100-240/277Vac, 50/60Hz			
Driver Suggest	INVENTRONICS			
Dimming	1-10V Dimming (Default) /Timer Dimming			
Surge Recommendation	10KV (Default) / 20KV (available on request)			
LED Type	LUMILEDS			
LED Quantities 3030	64	96	144	144
Pcb Input Current (3030)	48V 740mA	48V 1125mA	48V 1516mA	48V 1920mA
LED Quantities 5050	24	36	54	54
Pcb Input Current (5050)	48V 800mA	48V 1212mA	48V 1650mA	48V 2090mA
Lifetime	> 100, 000 hours -L ₇₀ , @25 °C (77 °F)			
Mounting	On pole with 76 mm top diameter, adaptor 60 mm top diameter can be chosen			
Material	Die casting with standard adc12 type aluminum, tempered glass, stainless 314 clips and screws. Clear polycarbonate with uv-resistant acrylic. Option for screen for asymmetrical light.			
Painting Color Suggest	RAL9005 Jet Black / Other Colors on request			
Available on request	NEMA socket (3/5/7pins), ZHAGA socket, Short cap, Photocell, NTC, OLC, DALI Dimming			
Weight	Net weight: 6.8kgs Gross weight: 8.8kgs		Net weight: 8.8kgs Gross weight: 10.5kgs	
Packing Size	365x365x720mm		460x460x920mm	

Smart Control System Optional



NEMA **Zhaga**


LoRa  **ZigBee**




IP66    **Constant current discharge**

Unit : mm

ZG-1094A



ZG-1094B



L ↔ N

6KV

L
N ↔ G

10KV